Office / Campus: MIMAROPA REGION CAMPUS						
Address / Cont	act Deta	ils: Brgy. Rizal, Odiongan, Romblon				
Supplier:		OCEAN DIVE SUPPLY PHILIPPINES, INC.		Inc. ii		
Address:		Brgy. Ibabao-Estancia, Mandaue City, Cebu		PO. No.:	-	5-P0035
TIN:		007-369-691-004		Mode of Procu		May-21 SVP
Gentlemen:					I CITICIL	SVP
Place of Deliver	rv.	Please furnish this Office the following articles subject to the terms and condition PSHS-MRC, Rizal, Odiongan, Rombion	s contained	herein:		
Date of Deliver		Paria-Mike, Rizal, Odiongan, Rombion		erm:	none	
Stock / V		2.750	Payment Term:		30 Days	
Property No.	Unit	Description	Quantity	Unit Cost	Total Cost	
Lot 1	set	DIVE REGULATOR (1st, 2nd, and Octopus)	6	B 10 700 00		
		* With certification that passed the European Standard for diving, currently	-	₱ 18,766.80	P	112,600.
		[EN250:2014"				
		* With certification that regulator was tested at depth 50msw with an air flow of				
		830 l/min at water temperature of 10°C. FIRST STAGE				
		UST Balanced diaphragm first stage.				
		A balanced, diaphragm design – provides consistent easy breathing from start				
		of dive until end.				
		1 HP port and 4 MP ports are available."				
		SECOND STAGE				
		Pneumatically-balanced second stage results in smooth, easy breathing				
		* The integrated venturi control provides a performance boost at depth while				
-		preventing unwanted freeflow at the surface				
		mouthpiece virtually eliminates jaw-fatigue." OCTOPUS				
-						
		Pneumatically-balanced second stage results in smooth, easy breathing.				
		The diver has full control of the venturi by means of a lever so as to prevent accidental freeforwards the extension of the venturi by means of a lever so as to prevent accidental freeforwards.				
		accidental freeflow when the octopus is not being used." TERMS AND CONDITIONS: (1) Products and all inclusions must be free from				
		defects in materials and workmanship. (2) Should have at least 1-yr warranty				
Lot 2	set	DIVE REGULATOR (Pressure and Depth Gauge)				
		The gauge case is made from nickel plated brass	6	₱ 6,981.00	P	41,886.0
		- Luminescent face up to 360 bars				
-		* The dial window is made of highly shock resistant material (anti-splinter				
		polycarbonate				
		A specially designed housing protects the gauge and HP hose fitting from				
		accidental damage				
		A large loop area designed into the housing allows for easy attachment.				
		There is an over-pressure capsule fitted in the back of the module to prevent				
		the screen from exploding in the unlikely event of the internal mechanism				
		Dials have a long phosphorescent effect for better reading in poor visibility				
		conditions				
		There are 2 attachment areas integrated into the design for position flexibility	-			
		This may be a compact design but the displays are vivid and clear – perfect				
		for diving. For example, the depth gauge spreads the first half of the scale and				
		In total shows a range down to 70 m.				
		Depth gauge has resettable max depth indicator"				
		TERMS AND CONDITIONS: (1) Products and all inclusions must be free from				
		defects in materials and workmanship. (2) Should have at least 1-yr warranty				
otal Amount in \	Manday	***Nothing Follows***				
		ONE HUNDRED FIFTY FOUR THOUSAND FOUR HUNDRED EIGHTY SIX PESC	S AND 80	0/100 ONLY	Р .	154,486.80
in case of ta fallvered item	Hure to	make full delivery within the time specified above, a penalty of one-tenth $(1/10)$ of one percent	for every da	ry of delay shall b	e imposed on t	the
Conforme	Per Contract of the Contract o					
comorme		/ \\i	ery truly yo	urs,		
		No ha		111		
		Elargeline E. targaro		- no		
		OCEAN DIVE SUPPLY PHILIPPINES, INC.		EDWARD C. A		
		Signature over Printed Name of Supplier		Campus D	n ector	
		June 03, 2021				
		· ·				
		Date		02-10110	1-2021-05-0	0498
d Cluster:		0	RS / DDC N-	06 404404	2024 05 00	100
ds Available:		P ky, 4ec. 80	no / DNO NO	.: 06-101101-	2021-05-004	198
as mydlidDle:		1,11,104,00	ate of ORS /	BRS No.: 5/2	5/ 2021	
		ARMAN .				
		IVY MAY F. FAMATIGA	mount:	PhP154,	486.80	
		1 CONTRACTOR OF				