

ELECTRIC NIBBLER (1 UNIT) ABC PHP 25,000.00

Features:

- Precise, burr-free curved and straight cuts from slim, yet powerful performer.
- Cuts flat and corrugated sheet metal with the same die.
- Die rotates 360degrees, large 1/4" stroke.
- Built-in thickness gauge for convenience.
- Continuous rating Input: 550W
- Capacity: Steel up to 400 N/mm² : 1.6mm
- Steel up to 600 N/mm² : 1.2mm
- Steel up to 800 N/mm² : 0.8mm
- Aluminum up to 200 N/mm² : 2.5mm
- Min. cutting radius: Outside edge : 50mm (2")
- Inside edge : 45mm (1-3/4")
- Strokes per minute (spm): 2,200
- Overall length: 261mm (10-1/4")
- Net Weight: 1.6kg (3.6lbs)
- Lifetime Service Warranty



POWER SHEARS (1 UNIT) ABC PHP 25,000.00

Features:

- Blade design results in no material loss.
- Body grip design with a paddle switch for easy one handed operation.
- Features a lower scrap guide to protect the operator's hands, a lock-off switch and built in thickness gauge.
- Easily replaceable blades with a total of 8 cutting edges each.
- Continuous rating Input: 300W
- Capacity: Steel up to 400 N/mm² : 1.6mm
- Steel up to 600 N/mm² : 1.2mm
- Steel up to 800 N/mm² : 0.8mm
- Aluminum up to 200 N/mm² : 2.5mm
- Min. cutting radius: 30mm (1-3/16")
- Strokes per minute (spm): 4,000
- Overall length
- Net Weight: 1.8kg (3.9lbs)
- Lifetime Service Warranty



CORE DRILL WITH RIG (2 UNITS) ABC PHP 50,000.00

Features:

Rated Power Input(W)	3300
No-Load Speed(r/min)	500
Max.Drilling Capacity(mm)	Φ200
Net Weight(kg)	22



BAND SAW (2 UNITS) ABC PHP 60,000.00

Features:

- Motor Power: 750w
- Table size: 352x352mm
- Throat: 352mm
- Cutting depth: 152mm
- Speed: 960m/min/800/min
- Blade size:2375x10x0.6m
- Lifetime Service Warranty



LADDER 25 FT (2 UNITS) ABC PHP 50,000.00

Features:

- Load Capacity: 300 lbs
- Reaches from 16 ft to an extendable length of 29 ft
- Self-leveling 2-way swivel safety shoes
- Main Material: Fiberglass
- Lifetime Service Warranty



BELT SANDER (2 UNITS) ABC PHP 50,000.00

Features

Auto-tracking belt system, high dust collecting capacity, low noise at only 85dB.

Unique design allows flush sanding to a wall with side of sander.

Electronic variable speed control feature.

Continuous rating Input: 1,010W

Belt size: 100 x 610mm (4"x 24")

Belt speed: 210 - 440m / min. (660 - 1,440ft/ min)

Overall length: 334mm (13-1/8")

Net Weight: 4.8kg (10.6lbs)

Power supply cord: 5.0m (16.4ft)

Lifetime Service Warranty



MAGNETIC DRILL PRESS (2 UNITS) ABC PHP 40,000.00

Features:

Compatible with Straight Shank Drill and Annular Cutter

No Load speed 330 rpm

Frequency 50 Hz

Magnetic Adhesion 13000 N

Weight 26.5 kg

Maximum Drilling Capacity 23 mm

Power Input 1200 W



MINI CHAINSAW (1 UNIT) ABC PHP 40,000.00

Features

36V slide Lithium-ion battery BSL3620 (2.0Ah) and Charger UC36YRSL

[Charging time: Approx. 60min.(BSL3620)]

Provides approx. 140 cuts per charge with BSL3620*¹

Guide bar length 300mm

Compact top handle design for more control

Mechanical kick-back brake

Toolless chain adjuster

LED light

Oil tank with backlight to easily check the remaining chain oil

Chain oil flow adjuster

Soft grip handle

Convenient retractable hook

Battery Voltage 36V

Guide Bar Length 300mm (12")

Chain Speed 8.3m/s

Type of Guide Bar Sprocket Nose

Chain Pitch 9.52mm (3/8")

Overall Length 618mm (24-5/16")

Weight 4.4kg (9.7lbs.) with BSL3620

Standard Battery (BSL3620), Charger (UC36YRSL), Chain Case, Round File

Accessories Chain Oil, Battery Cover



MULTITESTER (1 UNIT) ABC PHP 30,000.00

Digital Multimeter AC 1000V and DC1000V Temperature / Frequency Tester Meter DMM With Bag and TL75 Test Leads

Features:

Multiple functions with Auto / Manual ranges.

Large LCD display, 4,000 Counts update 3/sec

Main Measurements : Frequency, Temperature, AC/DC A-V-Ohm , capacitance, Diode & Continuity , duty cycle

Frequency :50Hz to 100Khz

Temperature :-55C to 400C

Capacitance :0.01nF to 100uF

AC Volts :0.1mV to 1,000V

DC Volts :0.1mV to 1,000V

AC Current :0.1uA to 10A

DC Current :0.1uA to 10A

Resistance :0.1 ohm to 40Mohm

Duty Cycle :0.1% to 99.9%

Data Hold Function

Both Auto range and Manual range Selectable

Overrange protection for all ranges

Polarity Indication : Indicates negative polarity

Overflow Indication

Sleep Mode / Auto Power off / Low Battery Indication

Major Specifications :

Frequency :50 / 500 / 5K /50K / 100KHz , +/- 0.1% + 3

Temperature :-55C to 400C , 2% to 9 % +/- 2C

Capacitance :50nF / 200nF / 2uF / 20uF / 200uF / 20mF , +/-2% +5

DC Volt :400mV / 4V / 40V / 400V / 1000V , +/-1.0% + 10

AC Volt :400mV / 4V / 40V / 400V / 1000V , +/- 3.0% + 3

DC Current :400uA / 4,000uA / 40mA / 400mA / 4A / 10A , +/- 1.5% + 3

AC Current :400uA / 4,000uA / 40mA / 400mA / 4A / 10A , +/- 1.5% + 3

Resistance :400 / 4K / 40K / 400K / 4M / 40M Ohm , +/- 0.5% + 3

Duty Cycle :0.1% to 99.9% , +/-1%

Continuity Test with Alert

Diode Test

17B+ With Bag and TL75 Probes

